

UASR (76x12 Displayed)

Utility Style, Aluminum Frame, Single Axle, Railside Trailer



-Standard Features and Equipment-

-6061 All Aluminum Frame	-2x10 Douglas Fir/Larch Plank Floor
-13.5" Side Height (Deck to top of Rail)	-5/16" x 30" Safety Chains, 7.6K lb Rating, with Safety Latch
-3500lb Straight Axle, Idler	-Folding Rear Ramp rated at 3000lbs
-Zinc-Plated Axle Mounting Brackets with Polypropylene Tape	-Ramp Unfolded Length: 54" L x 71" W (Ramp Width is trailer size - 5.00")
-4-Pin Flat, Easy Pull Electrical Connector	-Ramp Folds Down onto Deck
-2" Ball Coupler, Max rating 700lb tongue WT, with Polypropylene Tape	-2,000lb Lashing Rings , ZP (4 rings on 8' models, 6 on 10', 8 on 12', and 10 on 14')
-ST205/75R15 6-ply Radial Tires	-Spare Tire Mount (Changes from front to side depending on tool box)
-Modular-Style Steel Wheels, R15", 5 lug on 4.5" BHP, Black	-Deck to Ground Height: 18"
-LED Lighting Package	-Ground to Coupler Height: 15" When Level
-Enclosed Wiring, Protected with Tubing/Hose and Sealed with Silicone	-GVWR: 2,990lbs (3,500lbs with additional electric brake option)
-A-Frame Mounted Jack Rated at 5K lbs	

-Available Sizes-

Description	STD. Payload	Dry Wt.
UASR-60x08	2,440 lbs	550 lbs
UASR-60x10	2,365 lbs	625 lbs
UASR-60x12	2,290 lbs	700 lbs
UASR-66x08	2,340 lbs	650 lbs
UASR-66x10	2,270 lbs	720 lbs
UASR-66x12	2,195 lbs	795 lbs
UASR-76x10	2,225 lbs	765 lbs
UASR-76x12	2,130 lbs	860 lbs
UASR-76x14	1,915 lbs	1075 lbs
UASR-82x12	2,085 lbs	905 lbs
UASR-82x14	1,885 lbs	1105 lbs

-Available Options-

Description
Aluminum Wheel Upgrade PKG
Spare Wheel, Steel
Spare Wheel, Aluminum
Spray Shield, Rail Side, 60"
Spray Shield, Rail Side, 66"
Spray Shield, Rail Side 76"
Spray Shield, Rail Side, 82"
Extra Lashing Rings 2k lb
Jack Caster Wheel
Side Mount Pivot Jack
A-Frame Mounted, Lockable Handle Tool Box
Electric Braking Axle Upgrade

*Note: Payload is an estimated amount and actual may vary, refer to VIN tag for more info.