

## UASR-DR (76x12 Displayed)

Utility Style, Aluminum Frame, Single Axle, Railside Trailer with Drop in Side Ramps



### -Standard Features and Equipment-

|                                                                       |                                                                                |
|-----------------------------------------------------------------------|--------------------------------------------------------------------------------|
| -6061 All Aluminum Frame                                              | -2x10 Douglas Fir/Larch Plank Floor                                            |
| -13.5" Side Height (Deck to top of Rail)                              | -5/16" x 30" Safety Chains, 7.6K lb Rating, with Safety Latch                  |
| -3500lb Drop Axle, Idler                                              | -Folding Rear Ramp rated at 3000lbs                                            |
| -Zinc-Plated Axle Mounting Brackets with Polypropylene Tape           | -Ramp Unfolded Length: 54" L x 55" W (Ramp Width is trailer size - 5.00")      |
| -4-Pin Flat, Easy Pull Electrical Connector                           | -Ramp Folds Down onto Deck                                                     |
| -2" Ball Coupler, Max rating 700lb tongue WT, with Polypropylene Tape | -Side Loading Access w/ Drop in Ramp Gates, 1250 lb Capacity/Ea, 61" L x 13" W |
| -ST205/75R15 6-ply Radial Tires                                       | -2,000lb Lashing Rings , ZP (8 rings on 12' models, and 10 on 14')             |
| -Modular-Style Steel Wheels, R15", 5 lug on 4.5" BHP, Black           | -Spare Tire Mount (Changes from front to side depending on tool box)           |
| -LED Lighting Package                                                 | -Deck to Ground Height: 18"                                                    |
| -Enclosed Wiring, Protected with Tubing/Hose and Sealed with Silicone | -Ground to Coupler Height: 15" When Level                                      |
| -A-Frame Mounted Jack Rated at 5K lbs                                 | -GVWR: 2,990lbs (3,500lbs with additional electric brake option)               |

### -Available Sizes-

| Description                   | STD. Payload | Dry Wt.  |
|-------------------------------|--------------|----------|
| <a href="#">UASR-76x12-DR</a> | 2,040 lbs    | 950 lbs  |
| <a href="#">UASR-76x14-DR</a> | 1,870 lbs    | 1120 lbs |
| <a href="#">UASR-82x12-DR</a> | 2,005 lbs    | 985 lbs  |
| <a href="#">UASR-82x14-DR</a> | 1,700 lbs    | 1290 lbs |

### -Available Options-

| Description                               |
|-------------------------------------------|
| Aluminum Wheel Upgrade PKG                |
| Spare Wheel, Steel                        |
| Spare Wheel, Aluminum                     |
| Extra Lashing Rings 2k lb                 |
| Jack Caster Wheel                         |
| Side Mount Pivot Jack                     |
| A-Frame Mounted, Lockable Handle Tool Box |
| Electric Braking Axle Upgrade             |

\*Note: Payload is an estimated amount and actual may vary, refer to VIN tag for more info.