

## UATS (76x14 Displayed)

Utility Style, Aluminum Frame, Tandem Axle, Solid side Trailer



### -Standard Features and Equipment-

-6061 All Aluminum Frame	-A-Frame Mounted Jack Rated at 5K lbs
-13.5" Side Height (Deck to top of Flange)	-2x10 Douglas Fir/Larch Plank Floor
-Tandem 3500lb Drop Axles, Electric Brakes	-3/8" x 35" Safety Chains, 16.2K lb Rating, with Safety Latch
-Zinc-Plated Axle Mounting Brackets with Polypropylene Tape	-Folding Rear Ramp rated at 3000lbs
-7-Pin RV Style Electrical Connector	-Ramp Unfolded Length: 54" L x 71" W (Ramp Width is trailer size - 5.00")
-Junction Box, Break-away Kit with Battery and Charger	-Ramp Folds Down onto Deck
-2-5/16" Ball Coupler, Max 2,100lb tongue WT, with Polypropylene Tape	-4,000lb Lashing Rings , ZP(6 rings on 12' models, 6 on 14', 6 on 16', and 8 on 18')
-ST205/75R15 6-ply Radial Tires	-Spare Tire Mount (Changes from front to side depending on tool box)
-Modular-Style Steel Wheels, R15", 5 lug on 4.5" BHP, Black	-Deck to Ground Height: 18"
-LED Lighting Package	-Ground to Coupler Height: 15" When Level
-Enclosed Wiring, Protected with Tubing/Hose and Sealed with Silicone	-GVWR: 7000lbs

### -Available Sizes-

Description	Payload	Dry Wt.
UATS-76x12	5,705 lbs	1295 lbs
UATS-76x14	5,670 lbs	1330 lbs
UATS-76x16	5,635 lbs	1365 lbs
UATS-82x12	5,705 lbs	1295 lbs
UATS-82x14	5,597 lbs	1403 lbs
UATS-82x16	5,489 lbs	1511 lbs
UATS-82x18	5,380 lbs	1620 lbs

### -Available Options-

Description
Aluminum Wheel Upgrade PKG
Spare Wheel, Steel
Spare Wheel, Aluminum
Drop In Rear Panel, 76"
Drop In Rear Panel, 82"
Spray Shield, SS 76"
Spray Shield, SS, 82"
Extra Lashing Rings 4k lb
Recessed Lashing Rings 6k lb
Jack Caster Wheel
Side Mount Pivot Jack
Stabilizer Stands, Drop Leg
2-5/16" Adjustable Coupler
A-Frame Mounted, Lockable Handle Tool Box

\*Note: Payload is an estimated amount and actual may vary, refer to VIN tag for more info.