

## UATT (80x21 Displayed, AKA 80x18+3)

Utility Style, Aluminum Frame, Tandem Axle, Tilt Deck Car Hauler



### -Standard Features and Equipment-

-83" Between Fenders, 80" Narrowest Point of Tilt Deck, 18' Deck Area with 3' Knife Edge, 21' Overall Deck Length	-LED Lighting Package
-6061 All Aluminum Frame	-Enclosed Wiring, Protected with Tubing/Hose and Sealed with Silicone
-Gravity Tilting, With Hydraulic Damper and Locking Valve	-A-Frame Mounted Jack Rated at 5K lbs
-Tilt Loading Angle 9 Degrees	-2x8 Douglas Fir/Larch Plank Floor
13.5" Front Rail Height (Deck to top of Rail)	-3/8" x 35" Safety Chains, 16.2K lb Rating, with Safety Latch
-5200lb Dexter Torsion Drop Axles, with Electrical Self Adjusting Brakes	-Stake Pockets and Side Rub Rails
-7-Pin RV Style Arctic Rated Electrical Connector	-8x 4,000lb Lashing Ring, Zinc Plated
-Junction Box, Break-away Kit with Battery and Charger	-Spare Tire Mount (Changes from front to side depending on tool box)
-2-5/16" Ball Coupler, Max rating 2,100lb tongue WT, with Polypropylene Tape	-Deck to Ground Height: 20"
-ST225/75R15 7-ply Radial Tires	-Ground to Coupler Height: 17" When Level
-Modular-Style Steel Wheels, R15", 6 lug on 5.5" BHP, Black	-GVWR: 9,980lbs
	-Ship Weight: 2500lbs

### -Available Sizes-

Description	Payload	Dry Wt.
UATT-80x21	7240 lbs	2500 lbs

### -Available Options-

Description
Aluminum Wheel Upgrade PKG
Spare Wheel, Steel
Spare Wheel, Aluminum
Spray Shield, 82"
Extra Lashing Rings 4k lb
Recessed Lashing Rings 6k lb
Jack Caster Wheel
Side Mount Pivot Jack
2-5/16" Adjustable Coupler
Under Deck Winch Mount
Rail Cover (Stone Shield 15")
Lockable Handle Tool Box

\*Note: Payload is an estimated amount and actual may vary, refer to VIN tag for more info.